



Order form  
Orderer

Valid from November 2018  
Order no.

### DMT143L Dewpoint Transmitter (DMT242 Replacement)

Vaisala DRYCAP® Dewpoint Transmitter DMT143		1																		PRICE
1	Sensor and thread type	ISO G1/2" Probe with DRYCAP®180M Sensor NPT 1/2" Probe with DRYCAP®180M Sensor ISO G1/2" Probe with DRYCAP®180S Sensor NPT 1/2" Probe with DRYCAP®180S Sensor	L P R T																	
2	Digital interface	RS485 Modbus RTU (defaults: 19200, N, 8, 2, address 240)		1 2																
3	Analog signal output	None 4...20mA (3.6 mA error state) 4...20mA (0 mA error state)			0 C G															
4	Analog output scaling	None, metric units (analog signal output selection must be none) -80...+20°C Td (same as DMT242A scale) -80...+20°C Tda, dewpoint at ambient pressure NOTE: Please select U if non-metric units (°F) are needed for analog and/or digital output -60...+60°C Td (same as DMT242B scale) -50...+50°C Td (same as DMT242S scale) 0...1000 ppmv 0...5000 ppmv free scaling ppm Define scale: _____ free scaling Td °F Define scale: _____ free scaling Td °C Define scale: _____ free scaling %RH Define scale: _____		0 1 2 A B 3 4 P U X N																
5	Alarm LED setpoint	Off -40°C Td -20°C Td -10°C Td +3°C Td Other value Deactivated	Only fault indication Class 2 Class 3 Class 4 define value: °C Td LED always off		A B C D E X Z															
6	Process gas and chemical purge settings	Air for DRYCAP®180M Air for DRYCAP®180S Air for DRYCAP®180S with 12h purge interval, recommended				1 E F														
7	Pressure setting for optimized accuracy	1 bar (abs) 3 bar (abs) 5 bar (abs) 7 bar (abs) special (max 20 bar abs) Define value: bar			A B C D X															
8	Cable	No cable 0.3 m (1.0 ft) spare: HMP50Z032 3 m (9.8 ft) spare: HMP50Z30A 5 m (16.4 ft) spare: HMP50Z500 10 m (32.8 ft) spare: HMP50Z1000 1.5 m (4.9 ft) heavy duty cable spare: 225777 3 m (9.8 ft) heavy duty cable spare: 225229			0 2 3 4 5 6 7															
9	Sensor protection	Stainless steel sintered filter (38um) spare: HM47280SP Stainless steel filter for vacuum spare: HM47453SP				1 S														
10	Accessories	no accessories DMT242 to DMT143 cable adapter (spare: 247890SP) ONLY for ISO1/2" thread Basic sampling cell DMT242SC Sampling cell with swagelok 1/4" male connectors DMT242SC2 Sampling cell with quick connector and leak screw, DSC74 Two pressure sampling cell, DSC74B Two pressure sampling cell with cooling/venting coil, DSC74C Duct installation flange DM240FA Mounting nut NPT 1/2" adapter (spare: 210662SP)			0 A 1 2 3 4 5 6 7 8															
11	Package	Standard																		A
12	Identity	Vaisala																		S
13	User guide language	no user guide multilingual guide																		A X

TOTAL  
QTY  
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.  
Selections in *italic* are available at an extra price.

Example of order code with typical settings:

DMT143 L 1 C 1 A 1 A 3 1 0 A S X

Replacement	<b>DMT242A</b>	L	1	C	1	Z	1	A	0	1	A	A	S	X	
Examples:	<b>DMT242B</b>	L	1	C	A	Z	1	A	0	1	A	A	S	X	
	<b>DMT143</b>	<b>DMT242S</b>	R	1	C	B	Z	F	A	0	1	A	A	S	X

End customer: